

# ANYCERT-CCC-RVV

## RVV 多芯软导体聚氯乙烯绝缘护套电缆



### 应用

- 适用于一般电子、电器设备电源连线。

### 结构

- 单根或多股退火裸铜丝或镀锡铜丝绞合
- PVC 绝缘
- PVC 护套

### 特点

- 可通过 GB18380.1 垂直耐燃试验
- 使用标准厚度、易剥、易裁
- 具有抗酸碱、防霉、耐油、防潮、环保等特性

### 性能

- 额定电压：300/500V
- 额定温度：70℃

页码

编号	芯数 × 截面 mm <sup>2</sup>	绝缘厚度 mm	护套厚度 mm	平均外径		70℃时绝缘电阻最小值
				下限 mm	上限 mm	MΩ.km
1005RVV0020005	2 × 0.5	0.6	0.7	5.2	6.6	0.012
1005RVV00200075	2 × 0.75	0.6	0.8	5.7	7.2	0.012
1005RVV002001	2 × 1.0	0.6	0.8	5.9	7.5	0.010
1005RVV0020015	2 × 1.5	0.7	0.8	6.8	8.6	0.010
1005RVV0020025	2 × 2.5	0.8	0.9	8.2	10.3	0.012
1005RVV0030005	3 × 0.5	0.6	0.7	5.5	7	0.010
1005RVV00300075	3 × 0.75	0.6	0.8	6	7.6	0.010
1005RVV003001	3 × 1.0	0.6	0.8	6.3	8	0.011
1005RVV0030015	3 × 1.5	0.7	0.9	7.4	9.4	0.010
1005RVV0030025	3 × 2.5	0.8	1	9	11.2	0.010
1005RVV0040005	4 × 0.5	0.6	0.8	6.2	7.9	0.009
1005RVV00400075	4 × 0.75	0.6	0.8	6.6	8.3	0.007
1005RVV004001	4 × 1.0	0.6	0.8	6.9	8.7	0.006
1005RVV0040015	4 × 1.5	0.7	0.9	8.2	10.2	0.011
1005RVV0040025	4 × 2.5	0.8	1.1	10.1	12.5	0.010
1005RVV0050005	5 × 0.5	0.6	0.8	6.8	8.6	0.010
1005RVV00500075	5 × 0.75	0.6	0.9	7.4	9.3	0.009
1005RVV005001	5 × 1.0	0.6	0.9	7.8	9.8	0.007
1005RVV0050015	5 × 1.5	0.7	1	9.1	11.4	0.006
1005RVV0050025	5 × 2.5	0.8	1.1	11	13.7	0.011
1005RVV0050005	6 × 0.5	0.6	0.9	7.6	9.6	0.010
1005RVV00500075	6 × 0.75	0.6	0.9	8.1	10.1	0.010
1005RVV005001	6 × 1.0	0.6	1	8.7	10.8	0.009
1005RVV0050015	6 × 1.5	0.7	1.1	10.2	12.6	0.007
1005RVV0050025	6 × 2.5	0.8	1.2	12.2	15.1	0.006
1005RVV0070005	7 × 0.5	0.6	0.9	8.3	10.4	0.011

# ANYCERT-CCC-RVV

## RVV 多芯软导体聚氯乙烯绝缘护套电缆

编号	芯数 x 截面 mm <sup>2</sup>	绝缘厚度 mm	护套厚度 mm	平均外径		70°C时绝缘电阻最小值 MΩ.km
				下限 mm	上限 mm	
1005RVV00700075	7x0.75	0.6	1	9	11.3	0.010
1005RVV007001	7x1.0	0.6	1	9.5	11.8	0.010
1005RVV0070015	7x1.5	0.7	1.2	11.3	14.1	0.009
1005RVV0070025	7x2.5	0.8	1.3	13.6	16.8	0.007
1005RVV0120005	12x0.5	0.6	1.1	10.4	12.9	0.006
1005RVV01200075	12x0.75	0.6	1.1	11	13.7	0.011
1005RVV012001	12x1.0	0.6	1.2	11.8	14.6	0.010
1005RVV0120015	12x1.5	0.7	1.3	13.8	17	0.010
1005RVV0120025	12x2.5	0.8	1.5	16.8	20.6	0.009
1005RVV0180005	18x0.5	0.6	1.2	12.3	15.3	0.007
1005RVV01800075	18x0.75	0.6	1.3	13.2	16.4	0.006
1005RVV018001	18x1.0	0.6	1.3	14	17.2	0.011
1005RVV0180015	18x1.5	0.7	1.5	16.5	20.3	0.010
1005RVV0180025	18x2.5	0.8	1.8	20.2	24.8	0.010
1005RVV0270005	27x0.5	0.6	1.4	15.1	18.6	0.009
1005RVV02700075	27x0.75	0.6	1.5	16.2	19.9	0.007
1005RVV027001	27x1.0	0.6	1.5	17	21	0.010
1005RVV0270015	27x1.5	0.7	1.8	20.3	24.9	0.011
1005RVV0270025	27x2.5	0.8	2.1	24.7	30.2	0.011

\*可为客户提供特殊定做

